

# OS700 Contactless RFID Card Safe

### Electronic In-Room Safes

The Onity OS700 hotel in-room safe series features contactless RFID technology, following the latest market trends and demands. Operated by the room entry keycard, it is very easy to use and functional.

Combined with the proven reliability Onity solutions are known for, OS700 series safes are the ideal solution for properties looking to offer high security for their guests' belongings.

## **Features**

- □ User friendly, works approaching card to reader
- Reading technology: contactless RFID (ISO14443A, 14443B part 4, NFC)
- Supports MIFARE<sup>®</sup> Classic/EV1, Plus, Ultralight and Ultralight C cards
- Multiple opening devices available: cards, wristbands, keychains, etc.
- Non-volatile memory: records last 500 operations, including date, time and user
- □ Each new guest card overrides any previous ones
- □ Rental mode option at check-in
- □ Compatible with Onity OnPortal<sup>™</sup>, HT24W, OnPoint<sup>®</sup> and HT22 stand alone electronic locking systems
- □ Sleek modern design
- □ Mechanical key override
- □ 2 solid steel, anti-drill rotating bolts
- □ Interior carpet
- □ Low battery consumption
- Works with 4 AA standard batteries
- □ LEDs indicate status, including low battery
- Finishes: Black (standard) or Ivory
- □ Hand: Right (standard) or Left handed
- Power outlet option
- Interior shelf (Mini size only)

## **Portable Programmer Unit**

- Emergency Openings
- Password Protected
- Non-Resident Master Code
- Downloads audit trail (last 500 operations)



# Dimensions

### Mini size

 External Dimensions:
 250 x 350 x 250 mm (H x W x D)\*

 Volume:
 15.29 L

 Net Weight:
 10 Kg

 Door Opening:
 205 x 250 mm (H x W)

### Laptop size (standard)

External Dimension
Volume:
Net Weight:
Door Opening:

ns: 200 x 420 x 370 mm (H x W x D) \* 22.7 L 8.4 Kg 160 x 333 mm (H x W)

#### 17" Laptop size

 External Dimensions:
 200 x 508 x 370 mm (H x W x D)\*

 Volume:
 31.19 L

 Net Weight:
 16.5 Kg

 Door Opening:
 160 x 415 mm (H x W)

\* Depth indicates box dimensions, reader (20 mm) is not included.

### Certifications

- □ RED Directive 2014/53/EU
- □ RoHS Directive 2011/65/EU